

SuperKlean

Environmentally Exceptional Hot Water Sanitation Products

DuraFlow Dairy Spray Nozzles

Chemical and Bacteria Resistant

DH150D-DB (with 1/4" or 3/8" adapter)



Features

- Enhanced bacterial and chemical resistance.
- [Nozzle Chemical Resistance Guide](#)
- Built in nozzle wand with a 90° bend.
- Front trigger guard cover designed to prevent accidental spray.
- Trigger lock mechanism built in.

DH150D-R (with 1/4" or 3/8" adapter)



Technical Specifications

Inlet/Outlet Diameter: 1/2" NPT

Barb Fitting Diameter: 1/2" NPT x 3/4" HB

Nozzle Body: Stainless Steel. Epoxy resin coated.

Cartridge: Stainless Steel

Weight: 2.3 lbs

Recommended Operative Conditions

Maximum Pressure: 150 PSI

Maximum Temperature: 200 °F (93 °C)

SuperKlean

Environmentally Exceptional Hot Water Sanitation Products

DuraFlow Dairy Spray Nozzles

Chemical and Bacteria Resistant

Part #	Description
DH150D-DB-3/8	Dark blue dairy nozzle with 3/8" adapter
DH150D-DB-1/4	Dark blue dairy nozzle with 1/4" adapter
DH150D-R-3/8	Red dairy nozzle with 3/8" adapter
DH150D-R-1/4	Red dairy nozzle with 1/4" adapter
2-DHS	DuraFlow X lever, stainless steel. Plastic dip
3-DH	DuraFlow series nozzles lever bolt, Stainless steel
8-D	DuraFlow Dairy strainer screen
9-D-FC	Standard nozzle tip
9-D-FV1	High viscosity nozzle tip
9-D-FV2	Highest viscosity nozzle tip

2-DHS



3-DH



8-D



9-D-FC



9-D-FV1



9-D-FV2

